

DRILLING FLUIDS PRODUCT DATA
PAC L.V
Product Description:

PAC L.V is a low viscosity poly anionic cellulose, provides filtration control without significantly increasing viscosity. It could be used in fresh water to salt saturated waters.

Application:

- Fluid loss control.
- Wall – cake stabilization.
- Hole cleaning.

Typical Physical Properties:

MUD COMPOSITION					
COMPOSITION	1	2	3	4	
S.S.W ML	350	350	350	350	
PAC L.V GR	8	8	8	8	
LIMESTONE (P) GR	-	113	-	-	
BARITE GR	-	-	228	830	
FER-O-BAR GR	-	-	-	45	
LIME SOLUTION DROP	Few	Few	Few	Few	
DENSITY PCF	75	85	100	145	

TEST RESULTS AFTER ROLLING AT 300 °F FOR 4 HRS. READING RHEOLOGY AT 140 °F				
RESULTS	REQ	REQ	REQ	REQ
APP. VIS CPS	15	20	25	85
Y.P LBS/100FT2	2+	2+	2+	18+
GEL S. 10 Sec/10 min LBS/100FT2	1/2	1/2	1+/2+	2+/3+
pH	7-9.5	7-9.5	7-9.5	7-9.5
API. W.L ML	<15	<10	<5	<5
SETELLING NIL	NIL	NIL	NIL	NIL

PAC L.V Continue:

Recommended Treatment:

0.5 – 5 lb/bbl.

Source:

KPA

Packaging:

25 Kg Kraft bags with PE liner, palletized and shrink - wrapped.
Marked on: *Name of manufacturer, Batch No. and Production date.*

Safety Handling:

- Non – toxic.
- Keep in dry and sheltered place.



www.gempetrol.com
Info@gempetrol.com



+98 998 123 96 95
+971 55 694 76 35



Armenia office: Unit 15, No. : 86,Aram St.
Erevan, Armenia